



BS Semitrack

Conveyor belt lubricant.

BS Semitrack:

- economical lubricant for plastic conveyor belts;
- silicone emulsion based;
- good wetting and sliding properties;
- low foaming avoids problems in bottle control equipment;
- soluble in water of any hardness;
- BS Semitrack several times reduces water consumption for lubrication.

Product composition

Submitted in Safety data sheets.

Instructions for use

Before using **BS Semitrack**, it is recommended to wash the lubrication systems with an acid detergent, then rinse with water. The recommended concentration is 0.2 - 1.0%, the exact concentration is determined after evaluation of the lubrication equipment. **BS Semitrack** must not be mixed with other lubricants.

Information on safe use

Wear protective gloves / protective clothing / eye protection / face protection. Store in tightly closed original container in a dry, well-ventilated place. Do not store together with acids, hydroxides, oxidizers. Keep containers tightly closed. Store at a temperature not lower than + 5 ° C and not higher than + 35 ° C and away from heat sources. Follow general rules for handling chemicals. Do not mix with other chemicals.

Physical and chemical properties

State of aggregation	Liquid
Color	Unclear, white
Odor	Specific
pH, 100 %, 20-25°C	5,5 – 8,5
Realtive density, g/cm ³ , 20°C	0,99 - 1,01

Expiry date

18 months from the date of manufacture.